



Engineered for Safety!

## Pentalift Wheel Chock

Pentalift wheel chocks are an important component of the overall safety at the loading dock area. The wheel chocks secure the vehicles during the loading/off loading process. The wheel chocks are 7-1/2" high x 9" Long with a high friction base for improved locking grip. These wheel Chocks are a rugged design yet light-weight and easy to position/remove. An optional 18' zinc plated chain to secure wheel chock to dock area is available. A optional single or double wall bracket (not shown) is available for ease of storage when the wheel chock is not in use.



Consult a Pentalift Sales Representative for additional information or equipment recommendations

Note: Some photos may reflect products with optional features. All Pentalift Equipment products are subject to design improvement through modification without notice.

### **PENTALIFT EQUIPMENT CORPORATION**

P O Box 1510 Buffalo NY U.S.A. 14240-1510

P O Box 1060 Guelph ON Canada N1H 6N1

CP 1219 Pointe-Claire QC Canada H9S 5K7

Website: [www.pentalift.com](http://www.pentalift.com)

Phone (519) 763-3625 Fax (519) 763-2894

Phone (519) 763-3625 Fax (519) 763-2894

Phone (514) 426-0219 Fax (519) 763-2894

Email: [dock@pentalift.com](mailto:dock@pentalift.com)

Product Bulletin 0310D042