



Engineered for Safety!

Pentalift NLT-Series No Low Lift & Tilt Tables

Description:

Pentalift NLT-series no low lift & tilt tables are heavy-duty, hydraulic scissor lift tables with tilt platforms that permit floor level access to the lift platform. They are available in capacities from 2,500 to 6,000 lb. The NLT-series no low lift & tilt tables are available with platform sizes from 44" x 48" to 50" x 54". The travel height for the NLT-series is 34". The tilt platform can be specified to tilt up to 30 or 45 degrees. All NLT-series no low lift & tilt tables have a beveled edge on the approach end of the pan to make loading / unloading a smooth and easy operation.

Applications:

NLT-series no low lift & tilt tables are designed to meet the rugged demands of many industrial materials handling applications where loads need to be pushed or driven onto a floor level platform then lifted and tilted for easy access or positioning.



STANDARD FEATURES:

- Remote hydraulic power unit 1 ½ Hp 208-230-460-575/3/60 c/w TENV motor
- Reservoir is filled with oil
- Pre-wired NEMA 12 Motor Controls
- Pre-wired NEMA 12 push button on 10' of straight cord from power unit
- PentaFLOW bypass cylinder
- Beveled edge on approach end of pan
- Backstop 15" high x ½" thick
- Torsion tube to maintain even travel in event of slightly offset load
- Scissor legs are solid steel, one piece construction with precision reamed holes for accurate alignment and table operation
- Lubricated for life, maintenance free bearings at pivot points
- Highly visible detailed safety and operation decals for greater visibility and safety
- Finish coat of enamel paint-standard Pentalift gray

OPTIONS :

- Accordion bellows
- Photo Eye
- Larger platform sizes
- Velocity fuse
- Maintenance stand
- Up travel limit switch
- Guarded foot pedal control
- Additional voltage and horse power units
- Custom built sizes/lift

Consult a Pentalift Sales Representative for additional information or equipment recommendations

Note: Some photos may reflect products with optional features. All Pentalift Equipment products are subject to design improvement through modification without notice.

PENTALIFT EQUIPMENT CORPORATION

P O Box 1510 Buffalo NY U.S.A. 14240-1510
P O Box 1060 Guelph ON Canada N1H 6N1
CP 1219 Pointe-Claire QC Canada H9S 5K7
Website: www.pentalift.com

Phone (519) 763-3625 Fax (519) 763-2894
Phone (519) 763-3625 Fax (519) 763-2894
Phone (514) 426-0219 Fax (519) 763-2894
Email: lift@pentalift.com