

Pentalift Model PS 100 Fixed Head Pad Dock Seal

Designed for door openings up to 9' wide x 9' high



Considerations: Ideal dock height is 48"-50". Level vehicle approach is ideal. If approach is declined or inclined adjust bumper projection accordingly. Recommended side and head pad projection is 4"-6" beyond the face of the dock bumpers.

Features:

- Enviro-Green foam design scores LEED Certification credits
- Standard 12" high head pad
- Standard 12" face side pads
- Galvanized fasteners and hardware maintains building aesthetics
- Kiln dried quality wood backboard as standard
- Single base cover fabric
- Minimum of 3, 1½" diameter exhaust holes per side pad and head pad allows air to easily escape during vehicle positioning
- Evenly applied adhesive assures secure bonding of foam to backboard
- Full length 4" yellow guide stripes assists with proper vehicle positioning

Options:

- Fire retardant foam
- Pressure treated wood backboard
- Galvanized steel backing
- Wear pleats on face of dock seal provides added protection against wear
- Metal hood with gutter protects against snow build up and rain runoff
- Complete range of head pad designs to address specific application needs
- Beveled side pads
- Tapered side pads
- Bottom seal/ horizontal pad
- Fixed head pad drop curtains for lower trailers
- Build-out boxes for large projection applications
- Wide range of covering fabrics and colors