

Pentalift Model PS 200A Adjustable Curtain Dock Seal

Designed for door openings up to 9' wide x 10' high

Features:

- Enviro-Green foam design scores LEED Certification credits
- Standard 24" drop head curtain
- Structural steel rod sewn into top of head curtain provides weight to resist rain/snow build up
- 1" x 3" kiln dried wood attached to head curtain provides rigid installation onto building wall
- 2" tapered top on side pads ensures rain/snow run off
- Galvanized fasteners and hardware maintains building aesthetics
- Kiln dried quality wood backboard as standard
- Single base cover fabric
- Minimum of 3, 1½" diameter exhaust holes per side pad allows air to easily escape during vehicle positioning
- Evenly applied adhesive assures secure bonding of foam to backboard
- Full length 4" yellow guide stripes assists with proper vehicle positioning

Options:

- Fire retardant foam
- Pressure treated wood backboard
- Galvanized steel backing
- Wear pleats on face of dock seal provides added protection against wear
- Metal hood with gutter protects against snow build up and rain runoff
- Complete range of head curtain designs to address specific application needs
- Beveled side pads
- Tapered side pads
- Longer head curtains for lower trailers
- Build-out boxes for large projection applications
- Wide range of covering fabrics and colors



Considerations: Ideal dock height is 48"-50". Level vehicle approach is ideal. If approach is declined or inclined adjust bumper projection accordingly. Maximum recommended side pad projection is 4" - 6" beyond the face of the dock bumpers.