



Engineered for Safety

Pentalift DSL-Series Lift Tables

Description:

Pentalift DSL-series double scissor lift tables are hydraulic, heavy-duty, lift tables with load capacities ranging from 2,500 to 6,000 lb. Travel heights of 43", 52", 60", 79" or 90" are available. DSL-series lift tables feature a 12" to 16" low height. Standard platform sizes range from 24" x 36" to 42" x 72" (optional to 54" x 84").

Applications:

Pentalift DSL-series double scissor lift tables are suitable for higher lift applications, such as mezzanine access for storage or material transfer, where higher travel with a compact platform is required.



STANDARD FEATURES:

- Scissor legs are solid steel, one piece construction with precision reamed holes for accurate alignment and table operation
- Lubricated for life, maintenance-free bearing at pivot points
- PentaFLOW hydraulic bypass cylinders
- Remote hydraulic power unit
- 230-460-575/3/60 TEFC motor
- Pre-wired NEMA 12 motor control
- Pre-wired NEMA 12 push button control on 10' of straight cord
- Straight toe guards suitable for surface mounting
- Lagging brackets on frame
- Full width leg hinge pins
- Cross bracing between legs
- Top and bottom roller retainers
- Highly visible, detailed safety and operation decals for greater visibility and safety
- Table finished in Pentalift gray enamel

OPTIONS :

- Non-standard platform sizes
- Hydraulic power units up to 10 hp
- Accordion bellows
- Hydraulic velocity fuse
- Bevel toe guards
- Guarded foot pedal control
- Up travel limit switch
- Wall-mounted push button station
- Safety trip bars
- Sure stop valve

Consult a Pentalift Sales Representative for additional information or equipment recommendations

Note: Some photos may reflect products with optional features. All Pentalift Equipment products are subject to design improvement through modification without notice.

PENTALIFT EQUIPMENT CORPORATION

P O Box 1510 Buffalo NY U.S.A. 14240-1510

P O Box 1060 Guelph ON Canada N1H 6N1

Website: www.pentalift.com

Phone (519) 763-3625 Fax (519) 763-2894

Phone (519) 763-3625 Fax (519) 763-2894

Email: lift@pentalift.com

Product Bulletin 0214L030
Printed in Canada