

## Engineered for Safety

# Pentalift QSL-Series Lift Tables

### Description:

Pentalift QSL-series quadruple scissor lift tables are heavy-duty, high lift, hydraulic tables with lift capacities from 2,500 to 6,000 lb. Travel height of up to 240" can be specified. QSL series tables feature a low height of either 28" or 36".

## Applications:

Pentalift QSL-series quadruple scissor lift tables are used in small footprint, high lift applications to access mezzanine for processing, storage and/or material transfer.



#### STANDARD FEATURES:

- Scissor legs are solid steel, one piece construction with precision reamed holes for accurate alignment and table operation
- Lubricated for life, maintenance-free bearing at pivot points
- PentaFLOW hydraulic bypass cylinders
- Remote hydraulic power unit
- 230-460-575/3/60 TEFC motor
- Pre-wired NEMA 12 motor control
- Pre-wired NEMA 12 push button control on 10' of straight cord
- High pressure hose (with double steel braid)
- Straight toe guards suitable for surface mounting
- Lagging brackets on frame
- Full width leg hinge pin
- Top and bottom roller retainers
- Cross bracing between legs
- Integral maintenance stand
- Highly visible, detailed safety and operation decals for greater visibility and safety
- Table finished in Pentalift gray enamel

#### OPTIONS:

- Non-standard platform sizes
- Hydraulic power units up to 10 hp
- Accordion bellows
- Hydraulic velocity fuse
- Bevel toe guards (shown)
- Guarded foot pedal control
- Up travel limit switch
- Wall-mounted push button station
- Safety trip bars
- Sure stop valve

Consult a Pentalift Sales Representative for additional information or equipment recommendations Note: Some photos may reflect products with optional features. All Pentalift Equipment products are subject to design improvement through modification without notice.

#### PENTALIFT EQUIPMENT CORPORATION

P O Box 1510 Buffalo NY U.S.A. 14240-1510 P O Box 1060 Guelph ON Canada N1H 6N1 Website: www.pentalift.com Phone (519) 763-3625 Fax (519) 763-2894 Phone (519) 763-3625 Fax (519) 763-2894 Email: lift@pentalift.com

Product Bulletin 0214L032 Printed in Canada