



# Engineered for Safety

## Pentalift UE Upender

### Description:

Pentalift UE-series upenders are hydraulic, heavy-duty units with load capacities ranging from 2,500 to 6,000 lb. UE-series upenders facilitate a tilt angle of up to 90°. The standard platform size for the UE-Series upenders are: 36" x 36" x 36", 36" x 36" x 48" or 36" x 36" x 60". UE-series upenders feature a low height of 18".

### Applications:

Pentalift UE-series Upenders are engineered and designed to meet the needs of the steel, paper and other industries where a freestanding, heavy-duty upending table is required to orient or position coils, rolls or other heavy and awkward loads. A variety of custom options are available to meet the specific requirements of the application.



#### STANDARD FEATURES:

- Lubricated for life, maintenance-free bearings at pivot points
- Counter balanced valves hard plumbed to cylinder to prevent load runaway when tilting or in the event of hose failure
- Lagging holes in frame
- Self-contained 1 1/2 hp. hydraulic power unit
- 230-460-575/3/60 TENV motor
- Pre-wired NEMA 12 motor controls
- Pre-wired NEMA 12 push button on 10' of straight cord
- Temporary power wires
- Highly visible, detailed safety and operation decals for greater visibility and safety
- Upender finished in Pentalift gray enamel

#### OPTIONS:

- Hydraulic power units up to 5 hp.
- Non-standard platform sizes
- "V" groove in platform
- Pallet pocket
- Custom floor stands
- Movement indicators
- Wall-mounted push button station
- Guarded foot pedal control
- Upending warning alarm

Consult a Pentalift Sales Representative for additional information or equipment recommendations

Note: Some photos may reflect products with optional features. All Pentalift Equipment products are subject to design improvement through modification without notice.

## PENTALIFT EQUIPMENT CORPORATION

P O Box 1510 Buffalo NY U.S.A. 14240-1510

P O Box 1060 Guelph ON Canada N1H 6N1

Website: [www.pentalift.com](http://www.pentalift.com)

Phone (519) 763-3625 Fax (519) 763-2894

Phone (519) 763-3625 Fax (519) 763-2894

Email: [lift@pentalift.com](mailto:lift@pentalift.com)

Product Bulletin 0214L029  
Printed in Canada